


Flexible Coupling



Nominal Size mm/in	Pipe O.D mm/in	Working Pressure PSI/MPa	Bolt Size No.-Size mm	Dimensions mm/in		
				Ø	L	H
25 1	33.7 1.327	500 3.45	2-M10x45	60 2.362	98 3.858	43.5 1.713
32 1¼	42.4 1.669	500 3.45	2-M10x45	67 2.638	106 4.173	44 1.732
40 1½	48.3 1.900	500 3.45	2-M10x45	73 2.874	108 4.252	44 1.732
50 2	57.0 2.245	500 3.45	2-M10x55	83 3.268	122 4.803	45 1.772
50 2	60.3 2.375	500 3.45	2-M10x55	87 3.425	123 4.843	44 1.732
65 2½	73.0 2.875	500 3.45	2-M10x55	100 3.937	138 5.433	44 1.732
65 2½	76.1 3.000	500 3.45	2-M10x55	103 4.055	142 5.591	45 1.772
80 3	88.9 3.500	500 3.45	2-M12x60	117 4.606	166 6.535	45 1.772
100 4	108.0 4.250	500 3.45	2-M12x65	137 5.393	188 7.401	48 1.889
100 4	114.3 4.500	500 3.45	2-M12x65	139 5.472	190 7.480	49 1.929
125 5	133.0 5.250	400 2.75	2-M12x75	163 6.417	210 8.268	49 1.929
125 5	139.7 5.500	400 2.75	2-M12x75	168 6.614	218 8.583	49 1.929
150 6	159.0 6.250	400 2.75	2-M12x75	190 7.48	239 9.409	49 1.929
150 6	165.1 6.500	400 2.75	2-M12x75	193 7.598	241 9.488	49 1.929
150 6	168.3 6.625	400 2.75	2-M12x75	198.5 7.815	249 9.803	50 1.969
200 8	219.1 8.625	300 2.07	2-M16x85	253 9.961	320 12.598	59 2.323
250 10	273 10.748	300 2.07	2-M22x130	317 12.48	401 15.787	63 2.48
300 12	323.9 12.752	300 2.07	2-M22x130	375 14.764	455 17.913	64 2.52
350 14	355.6 14	300 2.07	3-M22x130	418 16.457	508 20	74 2.913
350 14	377 14.843	300 2.07	3-M22x130	441 17.362	535 21.063	78 3.071
400 16	406.4 16	300 2.07	3-M22x130	467 18.386	567 22.323	78 3.071
400 16	425.5 16.752	300 2.07	2-M22x130	486 19.134	580 22.835	78 3.071