



## VIZM.EX15240 Fittings, Rubber Gasketed

[Page Bottom](#)

### Fittings, Rubber Gasketed

[See General Information for Fittings, Rubber Gasketed](#)

#### WEIFANG 100TONG CASTING CO LTD

EX15240

1919 Airport South Rd  
Weicheng District  
Weifang, Shandong 261000 CHINA

#### Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT01	Rolled	T3091	1, 1-1/4, 1-1/2, 2, 3 OD, 3, 4	400
XGQT01	Rolled	T3091	5-1/2 OD, 6, 8 / 6 mm, 10 / 8 mm, 12 / 8 mm	300
XGQT01	Rolled	T3091-1993	6-1/2 OD	300
XGQT01	Rolled	T17395	2-1/2 / 4 mm, 4-1/4 OD / 4.5 mm	400
XGQT01	Rolled	T17395	5-1/4 OD / 5 mm, 5 / 4 mm, 6-1/4 OD / 6 mm	300
XGQT31	Rolled	5	1, 1-1/4, 1-1/2, 2	300
XGQT31	Rolled	WGalweld 7	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
XGQT31	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500
XGQT31	Rolled	10	4, 5, 6, 8, 10	300
XGQT31	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500
XGQT31	Rolled, Cut	40	4, 5, 6, 8, 10, 12	300
XGQT31	Rolled, Cut	GB/T17395	3 OD, 4-1/4 OD, 5-1/4 OD, 5-1/2 OD, 6-1/4 OD, 6-1/2 OD	300
XGQT31	Rolled, Cut	JIS G3452	216 mm	300

#### Flexible Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT02	Rolled	T3091	1, 1-1/4, 1-1/2, 2, 3 OD, 3, 4	400
XGQT02	Rolled	T3091	5-1/2 OD, 6, 8 / 6 mm, 10 / 8 mm, 12 / 8 mm	300
XGQT02	Rolled	T3091-1993	6-1/2 OD	300
XGQT02	Rolled	T17395	2-1/2 / 4 mm, 4-1/4 OD / 4.5 mm	400
XGQT02	Rolled	T17395	5-1/4 OD / 5 mm, 5 / 4 mm, 6-1/4 OD / 6 mm	300
XGQT32	Rolled	5	1, 1-1/4, 1-1/2, 2	300
XGQT32	Rolled	WGalweld 7	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
XGQT32	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500
XGQT32	Rolled	10	4, 5, 6, 8, 10	300
XGQT32	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500
XGQT32	Rolled, Cut	40	4, 5, 6, 8, 10, 12	300
XGQT32	Rolled, Cut	GB/T17395	3 OD, 4-1/4 OD, 5-1/4 OD, 5-1/2 OD, 6-1/4 OD, 6-1/2 OD	300
XGQT32	Rolled, Cut	JIS G3452	216 mm, 267 mm, 318 mm	300
XGQT02K	Rolled	10	2, 3, 4, 6	500
XGQT02K	Rolled	10	8	400

XGQT02K	Cut	40	2, 3, 4, 6	500
XGQT02K	Cut	40	8, 10, 12	400

**Reducing Coupling**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT02B	Rolled	T3091	2x1-1/2, 3 ODx1-1/2, 3 ODx2, 3x1-1/2, 3x2, 3x3 OD, 4x1-1/2, 4x2, 4x3 OD, 4x3, 6x3, 6x4, 8 / 6 mm x6	300
XGQT02B	Rolled	T17395xT3091	2-1/2 / 4 mm x1-1/2, 2-1/2 / 4 mm x2	300
XGQT02B	Rolled	T3091xT17395	3x2-1/2 / 4 mm, 4x2-1/2 / 4 mm	300

**Flange Adaptor**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT19	Rolled	T3091	2, 3 OD, 3, 4, 5-1/2 OD, 6, 8 / 6 mm	300
XGQT19	Rolled	T3091-1993	6-1/2 OD	300
XGQT19	Rolled	T17395	2-1/2 / 4 mm, 4-1/4 OD / 4.5 mm, 5-1/4 OD / 5 mm, 5 / 4 mm, 6-1/4 / 6 mm	300
XGQT29	Rolled	10, 40	2, 2-1/2, 3, 4, 5, 6, 8	300

**Side Outlet**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT03	Rolled	T3091	2x1, 2x1-1/4, 2x1-1/2, 3 ODx1, 3 ODx1-1/4, 3 ODx1-1/2, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 4x1, 4x1-1/4, 4x1-1/2, 4x2	300
XGQT03	Rolled	T3091	5-1/2 ODx1, 5-1/2 ODx1-1/4, 5-1/2 ODx1-1/2, 5-1/2 ODx2, 5-1/2 ODx3 OD, 6-1/2 ODx1, 6-1/2 ODx1-1/4, 6-1/2 ODx1-1/2, 6-1/2 ODx2, 6-1/2 ODx3 OD, 6-1/2 ODx3, 6x1, 6x1-1/4, 6x1-1/2, 6x2, 6x3 OD, 6x3, 8 / 6 mm x1, 8 / 6 mm x1-1/4, 8 / 6 mm x1-1/2, 8 / 6 mm x2, 8 / 6 mm x3 OD, 8 / 6 mm x3, 8 / 6 mm x4	300
XGQT03S	Threaded	T3091	1-1/2x1, 3 ODx2, 5x1, 5x1-1/4, 5x1-1/2, 5x2	232
XGQT03S	Threaded	T3091	2x1, 2x1-1/4, 2x1-1/2, 3 ODx1, 3 ODx1-1/4, 3 ODx1-1/2, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 4x1, 4x1-1/4, 4x1-1/2, 4x2, 5-1/2 ODx1, 5-1/2 ODx1-1/4, 5-1/2 ODx1-1/2, 5-1/2 ODx2, 5-1/2 ODx3 OD, 6-1/2 ODx1, 6-1/2 ODx1-1/4, 6-1/2 ODx1-1/2, 6-1/2 ODx2, 6-1/2 ODx3 OD, 6-1/2 ODx3, 6x1, 6x1-1/4, 6x1-1/2, 6x2, 6x3 OD, 6x3, 8 / 6 mm x1, 8 / 6 mm x1-1/4, 8 / 6 mm x1-1/2, 8 / 6 mm x2, 8 / 6 mm x3 OD, 8 / 6 mm x3, 8 / 6 mm x4	300
XGQT03U	Threaded	T3091	1x1/2, 1x3/4, 1-1/4x1/2, 1-1/4x3/4, 1-1/4x1, 1-1/2x1/2, 1-1/2x3/4, 1-1/2x1, 2x1/2, 2x3/4, 2x1, 3 ODx1/2, 3 ODx3/4, 3 ODx1	300
XGQT03U	Threaded	T17395	2-1/2 / 4 mm x1/2, 2-1/2 / 4 mm x3/4, 2-1/2 / 4 mm x1	300
XGQT33	Grooved	10, 40	2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2; 3 x 1-1/4, 1-1/2, 2; 4 x 1-1/4, 1-1/2, 2, 2-1/2; 5 x 1-1/2, 2, 2-1/2; 6 x 1-1/4, 1-1/2, 2, 2-1/2; 8 x 2, 2-1/2	300
XGQT33S	Threaded	10, 40	2 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 3 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2; 5 x 1, 1-1/4, 1-1/2, 2, 2-1/2; 6 x 1-1/4, 1-1/2, 2, 2-1/2	300

Models XGQT03S with 2 in. and larger main run size and 1 in. nominal outlets are intended for direct connection to sprinklers.

Models XGQT03U and XGQT33S in the 1/2, 3/4, 1 in. nominal outlets are intended for direct connection to sprinklers.

Models XGQT03, XGQT03S, XGQT03U, XGQT33 and XGQT33S in the 1 in. and larger nominal outlet sizes are intended for connection to system piping.

Note:

10 refers to Schedule 10 steel pipe in accordance with NFPA 13.

40 refers to Schedule 40 steel pipe in accordance with NFPA 13.

T3091 refers to GB/T3091-2001 ordinary steel pipe.

T3091-1993 refers to GB/T3091-1993 ordinary steel pipe.

T17395 refers to GB/T17395-1998 steel ordinary pipe.

6-1/2 OD pipe is GB/T3091-1993 pipe, 2-1/2", 4-1/4 OD, 5-1/4 OD, 5" and 6-1/4 OD pipes are GB/T17395-1998 pipes, the rest pipes are GB/T3091-2001 pipes.

5 refers to ASME B36.10-2004 ordinary steel pipe.

WGalweld 7 refers to Wuppermann Stahl GmbH, model WGalweld 7 (Galvanized) pipe, file number EX16421.

JIS G3452 refers to JIS G3452-2014 ordinary steel pipe.



Trademark and/or Tradename:

Last Updated on 2017-11-17

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".