

## VIZM.EX15240 - Fittings, Rubber Gasketed

## Fittings, Rubber Gasketed

[See General Information for Fittings, Rubber Gasketed](#)**WEIFANG 100TONG CASTING CO LTD**

1919 Airport South Rd  
Weicheng District  
Weifang, Shandong 261000 CHINA

**Coupling**

EX15240

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT01	Rolled	T3091	1, 1-1/4, 1-1/2, 2, 3 OD, 3, 4	400
XGQT01	Rolled	T3091	5-1/2 OD, 6, 8 / 6 mm, 10 / 8 mm, 12 / 8 mm	300
XGQT01	Rolled	T3091-1993	6-1/2 OD	300
XGQT01	Rolled	T17395	2-1/2 / 4 mm, 4-1/4 OD / 4.5 mm	400
XGQT01	Rolled	T17395	5-1/4 OD / 5 mm, 5 / 4 mm, 6-1/4 OD / 6 mm	300
XGQT01	Rolled	WGalweld 7	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
XGQT01	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500
XGQT01	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500
XGQT01	Rolled	10	4	400
XGQT01	Rolled, Cut	40	4	400
XGQT01	Rolled	10	5, 6, 8, 10, 12	300
XGQT01	Rolled, Cut	40	5, 6, 8, 10, 12	300
XGQT31	Rolled	5	1, 1-1/4, 1-1/2, 2	300
XGQT31	Rolled	WGalweld 7	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
XGQT31	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500
XGQT31	Rolled	10	4, 5, 6, 8, 10	300
XGQT31	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500
XGQT31	Rolled, Cut	40	4, 5, 6, 8, 10, 12	300

XGQT31	Rolled, Cut	GB/T17395	3 OD, 4-1/4 OD, 5-1/4 OD, 5-1/2 OD, 6-1/4 OD, 6-1/2 OD	300
XGQT31	Rolled, Cut	JIS G3452	216 mm	300
XGQT01P	Rolled	10	5	3448
XGQT01P	Rolled, Cut	40	5	3448
XGQT01P	Rolled	10	6, 8	3103
XGQT01P	Rolled, Cut	40	6, 8	3103
XGQT01P	Rolled	10	10, 12	2758
XGQT01P	Rolled, Cut	40	10, 12	2758
XGQT01P	Rolled, Cut	T3091	5-1/2OD	3448
XGQT01P	Rolled, Cut	T3091	6-1/2OD	3103
XGQT35	Rolled	5	2	300
XGQT35	Rolled	10	2, 2-1/2, 3	400
XGQT35	Rolled	10	4, 5, 6	300
XGQT35	Rolled, Cut	40	2, 2-1/2, 3	400
XGQT35	Rolled, Cut	40	4, 5, 6	300
XGQT35	Rolled	GB/T 3091	2, 2-1/2, 3	400
XGQT35	Rolled	GB/T 3091	4, 6-1/2OD	300
XGQT35	Rolled	WGalweld 7	2, 2-1/2, 3, 4	300
XGQT35	Rolled, Cut	GB/T 17395	5-1/2OD/4.5mm	300
XGQT35	Rolled, Cut	GB/T 17395	3OD/4mm	400
XGQT35	Rolled	GB/T 21835	6/4.5mm	300
31A	Rolled	5	1-1/4, 1-1/2, 2	300
31A	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	400
31A	Rolled	10	5, 6, 8, 10	300
31A	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	400
31A	Rolled, Cut	40	5, 6, 8, 10, 12	300
31A	Rolled	GB/T 3091	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	400
31A	Rolled	GB/T 3091	5-1/2OD, 6-1/2OD, 8	300
31A	Rolled	WGalweld 7	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
31A	Rolled, Cut	GB/T 17395	3OD/4mm, 4-1/4OD/4mm, 5-1/2OD/4.5mm, 6-1/4OD/5mm	300

31A	Rolled, Cut	JIS G3452	216.3mm, 267.4mm	300
31A	Rolled	GB/T 21835	6/4.5mm, 10/6.3mm, 12/7.1mm	300

**Flexible Coupling**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT02	Rolled	T3091	1, 1-1/4, 1-1/2, 2, 3 OD, 3, 4	400
XGQT02	Rolled	T3091	5-1/2 OD, 6, 8 / 6 mm, 10 / 8 mm, 12 / 8 mm	300
XGQT02	Rolled	T3091-1993	6-1/2 OD	300
XGQT02	Rolled	T17395	2-1/2 / 4 mm, 4-1/4 OD / 4.5 mm	400
XGQT02	Rolled	T17395	5-1/4 OD / 5 mm, 5 / 4 mm, 6-1/4 OD / 6 mm	300
XGQT02	Rolled	WGalweld 7	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
XGQT02	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500
XGQT02	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500
XGQT02	Rolled	10	4	400
XGQT02	Rolled, Cut	40	4	400
XGQT02	Rolled	10	5, 6, 8, 10, 12	300
XGQT02	Rolled, Cut	40	5, 6, 8, 10, 12	300
XGQT32	Rolled	5	1, 1-1/4, 1-1/2, 2	300
XGQT32	Rolled	WGalweld 7	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
XGQT32	Rolled	10	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500
XGQT32	Rolled	10	4, 5, 6, 8, 10	300
XGQT32	Rolled, Cut	40	1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500
XGQT32	Rolled, Cut	40	4, 5, 6, 8, 10, 12	300
XGQT32	Rolled, Cut	GB/T17395	3 OD, 4-1/4 OD, 5-1/4 OD, 5-1/2 OD, 6-1/4 OD, 6-1/2 OD	300
XGQT32	Rolled, Cut	JIS G3452	216 mm, 267 mm, 318 mm	300
XGQT02K	Rolled	10	2, 3, 4, 6	500
XGQT02K	Rolled	10	8	400
XGQT02K	Cut	40	2, 3, 4, 6	500
XGQT02K	Cut	40	8, 10, 12	400
XGQT02P	Rolled	10	5	500
XGQT02P	Rolled, Cut	40	5	500

XGQT02P	Rolled	10	6, 8	450
XGQT02P	Rolled, Cut	40	6, 8	450
XGQT02P	Rolled	10	10, 12	400
XGQT02P	Rolled, Cut	40	10, 12	400
XGQT02P	Rolled, Cut	T3091	5-1/2OD	500
XGQT02P	Rolled, Cut	T3091	6-1/2OD	450

**Reducing Coupling**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT02B	Rolled	T3091	2x1-1/2, 3 ODx1-1/2, 3 ODx2, 3x1-1/2, 3x2, 3x3 OD, 4x1-1/2, 4x2, 4x3 OD, 4x3, 6x3, 6x4, 8 / 6 mm x6	300
XGQT02B	Rolled	T17395xT3091	2-1/2 / 4 mm x1-1/2, 2-1/2 / 4 mm x2	300
XGQT02B	Rolled	T3091xT17395	3x2-1/2 / 4 mm, 4x2-1/2 / 4 mm	300
XGQT02B	Rolled, Cut	T3091	3ODx2-1/2	300
XGQT02B	Rolled	10	1-1/2x1-1/4; 2x1-1/2; 2-1/2x1-1/2, 2; 3x1-1/2, 2, 2-1/2; 4x1-1/2, 2, 2-1/2, 3	300
XGQT02B	Rolled, Cut	40	1-1/2x1-1/4; 2x1-1/2; 2-1/2x1-1/2, 2; 3x1-1/2, 2, 2-1/2; 4x1-1/2, 2, 2-1/2, 3	300

**Flange Adaptor**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
XGQT19	Rolled	T3091	2, 3 OD, 3, 4, 5-1/2 OD, 6, 8 / 6 mm	300
XGQT19	Rolled	T3091-1993	6-1/2 OD	300
XGQT19	Rolled	T17395	2-1/2 / 4 mm, 4-1/4 OD / 4.5 mm, 5-1/4 OD / 5 mm, 5 / 4 mm, 6-1/4 / 6 mm	300
XGQT29	Rolled	10, 40	2, 2-1/2, 3, 4, 5, 6, 8	300
XGQT29	Rolled	10, 40	10	175

**Side Outlet**

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
-------	-------------	------	------------	-----------------------

XGQT03	Rolled	T3091	2x1, 2x1-1/4, 2x1-1/2, 3 ODx1, 3 ODx1-1/4, 3 ODx1-1/2, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 4x1, 4x1-1/4, 4x1-1/2, 4x2	300
XGQT03	Rolled	T3091	5-1/2 ODx1, 5-1/2 ODx1-1/4, 5-1/2 ODx1-1/2, 5-1/2 ODx2, 5-1/2 ODx3 OD, 6-1/2 ODx1, 6-1/2 ODx1-1/4, 6-1/2 ODx1-1/2, 6-1/2 ODx2, 6-1/2 ODx3 OD, 6-1/2 ODx3, 6x1, 6x1-1/4, 6x1-1/2, 6x2, 6x3 OD, 6x3, 8 / 6 mm x1, 8 / 6 mm x1-1/4, 8 / 6 mm x1-1/2, 8 / 6 mm x2, 8 / 6 mm x3 OD, 8 / 6 mm x3, 8 / 6 mm x4	300
XGQT03	Grooved	10, 40	2-1/2 x 1; 4 x 2-1/2, 3OD, 3	300
XGQT03	Grooved	GB/T 3091	4 x 3OD, 3 5-1/2OD x 3; 6-1/2OD x 4	300
XGQT03S	Threaded	T3091	1-1/2x1, 3 ODx2, 5x1, 5x1-1/4, 5x1-1/2, 5x2	232
XGQT03S	Threaded	T3091	2x1, 2x1-1/4, 2x1-1/2, 3 ODx1, 3 ODx1-1/4, 3 ODx1-1/2, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 4x1, 4x1-1/4, 4x1-1/2, 4x2, 5-1/2 ODx1, 5-1/2 ODx1-1/4, 5-1/2 ODx1-1/2, 5-1/2 ODx2, 5-1/2 ODx3 OD, 6-1/2 ODx1, 6-1/2 ODx1-1/4, 6-1/2 ODx1-1/2, 6-1/2 ODx2, 6-1/2 ODx3 OD, 6-1/2 ODx3, 6x1, 6x1-1/4, 6x1-1/2, 6x2, 6x3 OD, 6x3, 8 / 6 mm x1, 8 / 6 mm x1-1/4, 8 / 6 mm x1-1/2, 8 / 6 mm x2, 8 / 6 mm x3 OD, 8 / 6 mm x3, 8 / 6 mm x4	300
XGQT03S	Threaded	10, 40	2-1/2 x 1-1/4; 4 x 2-1/2, 3OD, 3	300
XGQT03S	Threaded	GB/T 3091	4 x 3OD, 3 5-1/2OD x 3	300
XGQT03U	Threaded	T3091	1x1/2, 1x3/4, 1-1/4x1/2, 1-1/4x3/4, 1-1/4x1, 1-1/2x1/2, 1-1/2x3/4, 1-1/2x1, 2x1/2, 2x3/4, 2x1, 3 ODx1/2, 3 ODx3/4, 3 ODx1	300
XGQT03U	Threaded	T17395	2-1/2 / 4 mm x1/2, 2-1/2 / 4 mm x3/4, 2-1/2 / 4 mm x1	300
XGQT33	Grooved	10, 40	2 x 1-1/4, 1-1/2; 2-1/2 x 1-1/4, 1-1/2; 3 x 1-1/4, 1-1/2, 2; 4 x 1-1/4, 1-1/2, 2, 2-1/2; 5 x 1-1/2, 2, 2-1/2; 6 x 1-1/4, 1-1/2, 2, 2-1/2; 8 x 2, 2-1/2	300
XGQT33S	Threaded	10, 40	2 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 2-1/2 x 1/2, 3/4, 1, 1-1/4, 1-1/2; 3 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2; 4 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2; 5 x 1, 1-1/4, 1-1/2, 2, 2-1/2; 6 x 1-1/4, 1-1/2, 2, 2-1/2	300

All fitting models are suitable for use in dry pipe systems for temperatures to -40° F.

Models XGQT03S with 2 in. and larger main run size and 1 in. nominal outlets are intended for direct connection to sprinklers.

Models XGQT03U and XGQT33S in the 1/2, 3/4, 1 in. nominal outlets are intended for direct connection to sprinklers.

Models XGQT03, XGQT03S, XGQT03U, XGQT33 and XGQT33S in the 1 in. and larger nominal outlet sizes are intended for connection to system piping.

Note:

10 refers to Schedule 10 steel pipe in accordance with NFPA 13.

40 refers to Schedule 40 steel pipe in accordance with NFPA 13.

T3091 refers to GB/T3091 ordinary steel pipe.

T3091-1993 refers to GB/T3091-1993 ordinary steel pipe.

GB/T 3091 refers to GB/T3091 ordinary steel pipe.

T17395 refers to GB/T17395 steel ordinary pipe.

GB/T 17395 refers to GB/T 17395 steel ordinary pipe.

GB/T 21835 refers to GB/T 21835 ordinary steel pipe.

5 refers to ASME B36.10-2004 ordinary steel pipe.

WGalweld 7 refers to Wuppermann Stahl GmbH, model WGalweld 7 (Galvanized) pipe, file number EX16421.

JIS G3452 refers to JIS G3452-2014 ordinary steel pipe.

Trademark and/or Tradename: 

Last Updated on 2020-07-02

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"