Single Check Valves

Single check valves are used in fire protection systems to allow waterflow in one direction only. Typical applications are at connections between public water supplies and private fire service systems, at the discharge from fire pumps, at gravity tank connections and at fire service pumper connections.

Valves identified in the listing by a single asterisk (*) have side covers; valves identified by a double asterisk (**) have no removable covers; others have top covers. Clearance must be provided for side-cover valves to permit clapper removal. Valves without covers must be removed from the system for clapper replacement or repair. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Models AFCV-200, AFCV-300, AFCV-PN16

Product Specification

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
AFCV-200	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 6, 8, 10, 12	(50, 65, 80, 100, 150, 200, 250, 300)	200	(1375)	a
AFCV-PN16	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 6, 8, 10, 12	(50, 65, 80, 100, 150, 200, 250, 300)	232	(1595)	a
AFCV-300	Swing Check Valve Flanged Ends	2, 2 1/2, 3, 4, 6, 8, 10, 12	(50, 65, 80, 100, 150, 200, 250, 300)	300	(2065)	a

Remarks:
a. Resilient seat.

Company Name:	Haci Ayvaz Endüstriyel Mamülleri San. ve Tic. A.S.
Company Address:	Atatürk Sanayi Bölgesi Mustafa Inan Cad. No: 44, 34555 Hadimköy-Istanbul, Turkey
Company Website:	http://www.ayvaz.com
New/Updated Product Listing:	No
Listing Country:	Turkey
Certification Type:	FM Approved
Class of Work:	1210-Single Check Valves

© 2007-2022 FM Approvals. All rights reserved.