

for Commercial Suspended Ceilings

Flexible sprinkler hose with threaded end fittings are for use in commercial suspended ceilings. The flexible hoses are to be installed according to the manufacturer's directives.

Model ASH15-2025

1" inlet x 20 mm hose

Product Specification

Model No	NPT		K-Factor	Minimum Bend Radius		Number of Bends	Rated Working Pressure		Hose Assembly Length		Equivalent Length of 1 in. Schedule 40 Pipe	
	in	(mm)		in	(mm)		psi	(kPa)	in	(mm)	ft	(m)
ASH15-2025	1/2	(15)	5.6	8	(203)	1	232	(1595)	20	(500)	49.4	(15)
ASH15-2025	1/2	(15)	5.6	8	(203)	2	232	(1595)	28	(700)	70.3	(21.4)
ASH15-2025	1/2	(15)	5.6	8	(203)	3	232	(1595)	39	(1000)	101.6	(31.0)
ASH15-2025	1/2	(15)	5.6	8	(203)	3	232	(1595)	47	(1200)	122.5	(37.3)
ASH15-2025	1/2	(15)	5.6	8	(203)	3	232	(1595)	59	(1500)	153.8	(46.9)

3/4 inch (DN20) nominal diameter flexible metal hose for providing a connection to automatic sprinklers in commercial suspended ceilings. Approval is limited for use in commercial suspended ceilings with a bracket system manufactured by Hacı Ayvaz Endüstri Mamülleri San. ve Tic. A.Ş.

Model	Description
ASH15-2025	ASH: Ayvaz Sprinkler Hose 15: round Outlet 20: Hose size in mm 25: Inlet size in mm

Company Name:	Hacı Ayvaz Endüstriyel Mamülleri San. ve Tic. A.S.
Company Address:	Atatürk Sanayi Bölgesi Mustafa Inan Cad. No: 44, 34555 Hadimköy-İstanbul, Turkey
Company Website:	http://www.ayvaz.com
New/Updated Product Listing:	No
Listing Country:	Turkey
Certification Type:	FM Approved
Class of Work:	1637-Flex Spklr Hose with Ftngs