

## for Commercial Suspended Ceilings

Flexible sprinkler hose with threaded end fittings are for use in commercial suspended ceilings. The flexible hoses are to be installed according to the manufacturer's directives.

### Model ASH15E-2520

3/4" inlet x 25 mm hose

### Product Specification

Model No	NPT		K-Factor	Minimum Bend Radius		Number of Bends	Rated Working Pressure		Hose Assembly Length		Equivalent Length of 1 in. Schedule 40 Pipe	
	in	(mm)		in	(mm)		psi	(kPa)	in	(mm)	ft	(m)
Model ASH15E-2520	1/2	(15)	5.6	8	(203)	1	232	(1595)	20	(500)	18	(5.4)
Model ASH15E-2520	1/2	(15)	5.6	8	(203)	1	232	(1595)	28	(700)	22.7	(6.9)
Model ASH15E-2520	1/2	(15)	5.6	8	(203)	2	232	(1595)	39	(1000)	29.9	(9.1)
Model ASH15E-2520	1/2	(15)	5.6	8	(203)	3	232	(1595)	47	(1200)	34.6	(10.5)
Model ASH15E-2520	1/2	(15)	5.6	8	(203)	4	232	(1595)	59	(1500)	41.8	(12.7)
Model ASH15E-2520	1/2	(15)	5.6	8	(203)	4	232	(1595)	71	(1800)	48.9	(14.9)

1 inch nominal diameter flexible metal hose for providing a connection to automatic sprinklers in commercial suspended ceilings. Approval is limited for use in commercial suspended ceilings with a bracket system manufactured by Hacı Ayvaz Endüstriyel Mamüller San. Ve Tic. A.Ş.

Model	Description
Model ASH15E-2520	ASH: Ayvaz Sprinkler Hose 15: Round Outlet E: 90° Outlet Elbow 25: Hose size in mm 25: Inlet size in mm

<b>Company Name:</b>	Hacı Ayvaz Endüstriyel Mamülleri San. ve Tic. A.S.
<b>Company Address:</b>	Atatürk Sanayi Bölgesi Mustafa Inan Cad. No: 44, 34555 Hadimköy-Istanbul, Turkey
<b>Company Website:</b>	<a href="http://www.ayvaz.com">http://www.ayvaz.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	Turkey
<b>Certification Type:</b>	FM Approved
<b>Class of Work:</b>	1637-Flex Spklr Hose with Ftngs